

### Amendments to the Claims

This listing of claims will replaced all prior versions, and listings, of claims in the application.

Claims 1 - 14 (Canceled).

1 Claim 15 (Previously presented) A non-linear magnetic harmonic motion converter  
2 apparatus comprising:

3 a plurality of gimbal supported ring magnets disposed in spaced apart concentric  
4 orientation within a frame member, each gimbal supported ring magnet are disposed  
5 within said frame member to reciprocate about an axial shaft disposed through a  
6 central portion of said frame member, each gimbal supported ring magnet having a  
7 gimbal magnet field of sufficient strength to extend to said axial shaft;

8 a plurality of electromagnets disposed in spaced apart orientation on an inner  
9 perimeter of said frame member, each of said plurality of electromagnets having an  
10 electrical circuit means powered by an electric power source connected thereto, said  
11 electrical circuit means provides electric power from the electric power source in a timed  
12 sequence to alternate the magnetic poles of each of said plurality of electromagnets  
13 resulting in reciprocation of each gimbal supported ring magnet and repositioning of  
14 each gimbal magnet field in relation to said axial shaft; and

15 at least one pair of rotor magnets disposed on said axial shaft, said at least one  
16 pair of rotor magnets disposed in opposed orientation on said axial shaft, said at least  
17 one pair of rotor magnets rotates in unison with said axial shaft, each rotor magnet  
18 having a rotor magnet field defined by respective north and south poles oriented in a  
19 circumferential path of rotation about said axial shaft with said rotor magnet field

20 directed substantially perpendicular to the axis of rotation of said axial shaft, said rotor  
21 magnet field is alternately attracted to and repelled from each gimbal magnet field upon  
22 repositioning of each gimbal supported ring magnet by the alternation of the magnetic  
23 poles of each of said plurality of electromagnets.

1 16. (Previously presented) The apparatus of Claim 15 wherein said at least one  
2 rotor magnet includes a plurality of pairs of rotor magnets positioned in spaced apart  
3 configuration along said axial shaft, each pair of said plurality of pairs of rotor magnets  
4 are separated by an angle of separation in a range between about 90 degrees of  
5 separation to about 180 degrees of separation.

1 17. (Previously presented) A non-linear magnetic harmonic pump including a  
2 housing having a plurality of fluid channels therein, the plurality of fluid channels  
3 including at least one inlet fluid channel and at least one output fluid channel,  
4 comprising:  
5 a plurality of rotor magnet units disposed within the housing, each rotor magnet  
6 unit including an axial shaft disposed within each one of a plurality of radially oriented  
7 fluid channels connected between the plurality of fluid channels, each radially oriented  
8 fluid channel is in fluid communication with the at least one inlet fluid channel and  
9 with the at least one output fluid channel within the housing, each rotor magnet unit  
10 further including:  
11 a plurality of impeller fins interconnected at a base end of each impeller fin to  
12 rotate around said axial shaft, each impeller fin having distal ends rotating around said  
13 axial shaft for transfer of fluid through each respective radially oriented fluid channel;  
14 and

at least one rotor magnet extended in a radial configuration interdisposed between said plurality of impeller fins, said at least one rotor magnet rotatable around said axial shaft in unison with said plurality of impeller fins, said at least one rotor magnet including respective north and south poles oriented in a circumferential path of rotation about said axial shaft with the net flux fields of the north and south poles directed substantially perpendicular to the axis of rotation of said axial shaft; and a plurality of gimbal lever magnets disposed to extend in a radial configuration from a central gimbal supported pivot axis, each gimbal lever magnet disposed in spaced-apart orientation between respective pairs of said plurality of rotor magnet units, said plurality of gimbal lever magnets are each reciprocatingly moved in a non-linear path relative to the central gimbal supported pivot axis, each gimbal lever magnet having a gimbal magnet field disposed between a north and a south magnet pole of each gimbal lever magnet; whereby each rotor magnet unit rotates about each respective axial shaft upon the influence on the net flux fields of the north and south poles of each respective rotor magnet by the movement of the gimbal magnet field of each gimbal lever magnet disposed between respective pairs of rotor magnet units, with pumping of fluids through each respective fluid channel from the at least one inlet fluid channel and toward the at least one output fluid channel of the pump.

18. (Previously presented) A non-linear magnetic harmonic pump including a housing having a plurality of fluid channels therein, the plurality of fluid channels including at least one inlet fluid channel and at least one output fluid channel, comprising:

a plurality of stator magnets disposed in spaced-apart orientation along a perimeter of a housing, each stator magnet having a north and a south magnet pole

7 having respective north and south magnetic fields;

8 a plurality of rotor magnet units disposed within the housing, each rotor magnet  
9 unit including an axial shaft disposed within each one of a plurality of radially oriented  
10 fluid channels connected between the plurality of fluid channels, each radially oriented  
11 fluid channel is in fluid communication with the at least one inlet fluid channel and  
12 with the at least one output fluid channel within the housing, each rotor magnet unit  
13 further including:

14 a plurality of impeller fins interconnected at a base end of each impeller fin to  
15 rotate around said axial shaft, each impeller fin having distal ends rotating around said  
16 axial shaft for transfer of fluid through each respective radially oriented fluid channel;

17 at least one rotor magnet extended in a radial configuration interdisposed  
18 between said plurality of impeller fins, said at least one rotor magnet rotatable around  
19 said axial shaft in unison with said plurality of impeller fins, said at least one rotor  
20 magnet including a rotor magnet field defined by respective north and south poles  
21 oriented in a circumferential path of rotation about said axial shaft with the net flux  
22 fields of the north and south poles directed substantially perpendicular to the axis of  
23 rotation of said axial shaft;

24 a plurality of gimbal lever magnets disposed to extend in a radial configuration  
25 from a central gimbal supported pivot axis, each gimbal lever magnet disposed in  
26 spaced-apart orientation between respective pairs of said plurality of rotor magnet  
27 units, said plurality of gimbal lever magnets are each reciprocatingly moved in a non-  
28 linear path relative to the central gimbal supported pivot axis, each gimbal lever magnet  
29 having a gimbal magnet field disposed between a north and a south magnet pole of each  
30 gimbal lever magnet; and

31 a plurality of electromagnets disposed in spaced apart orientation within said  
32 housing, each electromagnet is interdisposed between each rotor magnet unit, each

electromagnet connected to an electric power source and a control means providing electric power in a timed sequence to each electromagnet to alternate the magnetic poles of each electromagnet;

whereby each rotor magnet unit rotates about each respective axial shaft upon the influence on the rotor magnet field of each respective rotor magnet by the attracting and repelling of the magnet fields of each stator magnet disposed along the perimeter of the housing, by the alternating of the magnetic poles of each electromagnet, and by the movement of the gimbal magnet field of each gimbal lever magnet with resulting pumping of fluids through each respective fluid channel from the at least one inlet fluid channel and toward the at least one output fluid channel of the pump.

19. (Previously presented) A non-linear magnetic harmonic electric generator including a housing having a plurality of channels therein, said electric generator including electromagnetic induction elements interdisposed between the plurality of channels and circuitry interconnected with the electromagnetic induction elements, said electric generator comprising:

a central magnet supported in a gimbal configuration, said central magnet is reciprocatingly moved in a non-linear path relative to the housing, said central magnet having a central magnetic field defined by the north and south magnet poles oriented on respective inner and outer perimeters of said central magnet to form a central magnetic field; and

a plurality of rotor magnet units disposed within the housing, each rotor magnet unit including an axial shaft disposed within each one of a plurality of radially oriented channels of the plurality of channels, each radially oriented channel is adjacent at least one of the electromagnetic induction elements, each rotor magnet unit further including:

16 at least one rotor magnet rotatable around said axial shaft, each rotor  
17 magnet including a rotor magnet field defined by respective north and south  
18 poles oriented in a circumferential path of rotation about said axial shaft with the  
19 net flux fields of the north and south poles directed substantially perpendicular  
20 to the axis of rotation of said axial shaft;

21 whereby rotation occurs for each rotor magnet unit about each respective axial  
22 shaft upon the influence on the rotor magnet field of each respective rotor magnet by  
23 the movement of the central magnetic field of the central magnet along with the  
24 alternation of the magnetic poles of each electromagnet, the rotation of each rotor  
25 magnet unit induces rotation of each respective axial shaft for activation of circuitry for  
26 the production of electricity.

1 20. (Previously presented) A non-linear magnetic harmonic electric generator  
2 including a housing having a plurality of channels therein, said electric generator  
3 including magnetic induction elements interdisposed between the plurality of channels  
4 and circuitry interconnected with the magnetic induction elements, said electric  
5 generator comprising:

6 a central magnet supported in a gimbal configuration, said central magnet is  
7 reciprocatingly moved in a non-linear path relative to the housing, said central magnet  
8 having a central magnetic field defined by the north and south magnet poles oriented  
9 on respective inner and outer perimeters of said central magnet to form a central  
10 magnetic field;

11 a plurality of stator magnets disposed in spaced-apart orientation along a  
12 perimeter of a housing, each stator magnet having a north and a south magnet pole  
13 having respective north and south magnetic fields; and

14 a plurality of rotor magnet units disposed within the housing, each rotor magnet

unit including an axial shaft disposed within each one of a plurality of radially oriented channels of the plurality of channels, each radially oriented channel is adjacent at least one of the magnetic induction elements, each rotor magnet unit further including:

at least one rotor magnet rotatable around said axial shaft, each rotor magnet including a rotor magnet field defined by respective north and south poles oriented in a circumferential path of rotation about said axial shaft with the net flux fields of the north and south poles directed substantially perpendicular to the axis of rotation of said axial shaft;

whereby rotation occurs for each rotor magnet unit about each respective axial shaft upon the influence on the rotor magnet field of each respective rotor magnet by the attracting and repelling of the magnet fields of each stator magnet and by the movement of the central magnetic field, the rotation of each rotor magnet unit produces rotation of each respective axial shaft for activation of circuitry attached to each respective axial shaft for the production of electricity.